

## K-Jaw Belt Clamps



For Pulling Belt – 1360kgs (3,000 lbs) pull rating

### Key Benefits:

- Easy to use
- Conveyor belt does not have to be flat to install
- Light weight
- Cast steel for strength
- Can be pulled across top rollers
- Very economical because they fit all belt widths
- Fits belt with thicknesses up to approx 15mm (5/8")
- Cost less than other belt clamps



## K-Jaw Belt Clamps

### RECOMMENDED CARE, MAINTENANCE, AND USE OF TDT BELT CLAMPS

#### SAVE FOR FUTURE REFERENCE

The following guidelines should be followed in order to help maintain all clamps in good condition:

1. Clean the surfaces of the clamps anytime there is an accumulation of foreign material. Use a clean wire brush to clean the clamps.
2. Clean all working parts with an appropriate cleaner/degreaser.
3. *Never repair or modify any clamp.* If there is ever any question about the safe condition of any clamp, please consult us directly.

OSHA requires that all hand tools and equipment be maintained in good working order and that they be free from damage caused by wear or abuse (OSHA Part 1910, Subpart P, Section 1910.242)

In addition, OSHA Part 1926, Subpart V, Section 1926.955, paragraphs (c)(7)(ii) and (8) specifically state that:

“The manufacturer’s load rating shall not be exceeded for stringing lines, pulling lines, sock connections, and all load-bearing hardware and accessories.”

**⚠ WARNING** Proper maintenance and field inspection of all clamps is necessary before each use.

- Check mechanical condition of entire clamp.
- Check all parts for distortion or misalignment.
- Do not exceed rated capacity of 1.5 tons.
- Do not use without safety cable or safety chain.
- Always use in pairs.

#### Repair or Replace?

*Never attempt to repair or modify any clamp. Clamps that are bent, misaligned or otherwise distorted should be discarded and replaced.*

**⚠ WARNING**

- Clamps are to be used for temporary installation, not for permanent anchorage.
- Always lift and secure counterweight.
- Always pull in a line parallel to belt.
- Before each use clean jaw area and inspect clamp for proper operation to avoid slippage.
- Do not exceed rated capacity of 1.5 tons.
- Do not use without safety cable or safety chain.
- Always use in pairs.

\* Any modification of this product is un-authorized and potentially dangerous. MATO Corporation assumes no liability for any accident or injury occurring in the use of this product in any modified form, or in any manner inconsistent with its intended use or design.

U.S. PATENT PENDING

Page 2



abn 28 006 489 238

[www.kinder.com.au](http://www.kinder.com.au)

**Kinder Australia Pty Ltd**

P | +61 3 8587 9111 F | +61 3 8587 9101 E | [sales@kinder.com.au](mailto:sales@kinder.com.au)

26 Canterbury Rd, Braeside VIC 3195 (PO Box 1026, Braeside VIC 3195)

**Subject to © Kinder Australia Pty Ltd**

