

Skirting Rubber





<u>Skirting rubber</u> is a multi- purpose rubber used as a sealing solution for all conveyor applications. Available in full width slabs up to 1500mm wide, and also in pre-cut skirting strips, making it suitable for all belt widths and trough angles.

Skirting rubber is available in various rubber compounds, thicknesses and widths in standard 30m rolls. It can also be supplied in shorter lengths or cut down to size, depending on the size of the belt.

Skirting rubber must be adjusted periodically, in order to make an effective seal that will prevent dust leakage and material spillage.





https://kinder.com.au

Subject to © Kinder Australia Pty Ltd Issue: 202102

Kinder Australia Pty Ltd

26 Canterbury Road, Braeside VIC 3195 PO Box 1026, Braeside VIC 3195

≅ +61 3 8587 9111 **⊒** +61 3 8587 9101

⁴ conveyorsolutions@kinder.com.au ABN: 28 006 489 238





Skirting Rubber

The following compounds and thicknesses available in our skirting rubber product range are: Black Skirting Rubber 65 Duro is suitable for a harder, less flexible rubber skirt seal.

Thickness (mm)	Roll Length (m)	Stock Width (mm)								
		50	75	100	125	150	200	250	300	1500
6.0	30	✓	✓	✓	✓	✓	✓	✓	✓	✓
9.0	30	√	√	√	√	√	√	√	√	√
12.0	30	√	√	√	√	√	√	√	√	√
16.0	30	√	√	√	√	√	√	√	√	√
19.0	30	√	√	√	√	√	√	√	√	√
25.0	10	√	√	√	√	√	√	√	√	√

Soft Skirting Rubber 40 Duro, is suitable for a softer and more flexible rubber skirt seal.

Thickness (mm)	Roll Length (m)	Stock Width (mm)								
		50	75	100	125	150	200	250	300	1500
6.0	30	✓	~	✓	√	✓	✓	√	✓	~
9.0	30	√	√	✓	√	√	√	√	√	√
12.0	30	√	√	√	√	✓	√	√	√	√
16.0	30	√	√	✓	√	√	√	√	√	√
19.0	30	√	√	√	√	√	√	√	√	√

Further compounds and thicknesses available in our skirting rubber product range are:

- FRAS Skirting Rubber is a neoprene rubber commonly used for skirting that is exposed to high temperatures; (Suitable for most applications and available in 6-19mm Thicknesses x 30m Rolls and 50-1500mm Widths)
- Neoprene skirting rubber is a heat and wear resistant rubber that enhances the wear life of the skirt. (Available in 6-25mm Thicknesses x 30m Rolls and 50-1500mm Widths)

All above standard 30m Rolls can be supplied in shorter lengths and cut to size to fit custom requirements. POA.



https://kinder.com.au

Subject to © Kinder Australia Pty Ltd Issue: 202102

Kinder Australia Pty Ltd

26 Canterbury Road, Braeside VIC 3195 PO Box 1026, Braeside VIC 3195

≅ +61 3 8587 9111 **≘** +61 3 8587 9101

⊕ conveyorsolutions@kinder.com.au ABN: 28 006 489 238

